

QN0805X474J3950FB

R25=470kΩ±5%， B25/50=3950±1%， B25/85=3987

温度 Temp. (°C)	R 最小值 R_Min (Kohm)	R 中心值 R_Cent (Kohm)	R 最大值 R_Max (Kohm)	阻值公差 Res TOL.	温度公差 Temp. TOL.(°C)
-40	14,880.061	16,227.916	17,653.617	8.79%	1.26
-39	13,920.457	15,171.171	16,492.922	8.71%	1.26
-38	13,029.302	14,190.462	15,416.466	8.64%	1.26
-37	12,201.265	13,279.820	14,417.582	8.57%	1.26
-36	11,431.466	12,433.786	13,490.180	8.50%	1.26
-35	10,715.434	11,647.358	12,628.682	8.43%	1.26
-34	10,049.060	10,915.949	11,827.976	8.35%	1.26
-33	9,428.589	10,235.361	11,083.387	8.29%	1.26
-32	8,850.559	9,601.733	10,390.619	8.22%	1.26
-31	8,311.801	9,011.530	9,745.740	8.15%	1.25
-30	7,809.396	8,461.500	9,145.135	8.08%	1.25
-29	7,340.661	7,948.653	8,585.484	8.01%	1.25
-28	6,903.130	7,470.244	8,063.739	7.94%	1.25
-27	6,494.526	7,023.742	7,577.092	7.88%	1.25
-26	6,112.761	6,606.824	7,122.968	7.81%	1.25
-25	5,755.902	6,217.344	6,698.989	7.75%	1.25
-24	5,421.453	5,852.543	6,302.115	7.68%	1.25
-23	5,108.607	5,511.511	5,931.324	7.62%	1.25
-22	4,815.835	5,192.551	5,584.740	7.55%	1.24
-21	4,541.725	4,894.101	5,260.633	7.49%	1.24
-20	4,284.972	4,614.714	4,957.407	7.43%	1.24
-19	4,044.371	4,353.057	4,673.590	7.36%	1.24
-18	3,818.806	4,107.894	4,407.819	7.30%	1.24
-17	3,607.250	3,878.090	4,158.841	7.24%	1.24
-16	3,408.745	3,662.586	3,925.491	7.18%	1.24
-15	3,222.408	3,460.407	3,706.694	7.12%	1.23
-14	3,047.421	3,270.651	3,501.458	7.06%	1.23

温度 Temp. (°C)	R 最小值 R_Min (Kohm)	R 中心值 R_Cent (Kohm)	R 最大值 R_Max (Kohm)	阻值公差 Res TOL.	温度公差 Temp. TOL.(°C)
-13	2,883.023	3,092.478	3,308.857	7.00%	1.23
-12	2,728.514	2,925.116	3,128.043	6.94%	1.23
-11	2,583.237	2,767.841	2,958.222	6.88%	1.23
-10	2,446.588	2,619.987	2,798.662	6.82%	1.23
-9	2,318.001	2,480.933	2,648.681	6.76%	1.22
-8	2,196.956	2,350.107	2,507.649	6.70%	1.22
-7	2,082.965	2,226.971	2,374.980	6.65%	1.22
-6	1,975.578	2,111.031	2,250.131	6.59%	1.22
-5	1,874.374	2,001.824	2,132.595	6.53%	1.22
-4	1,778.829	1,898.779	2,021.750	6.48%	1.21
-3	1,688.733	1,801.662	1,917.336	6.42%	1.21
-2	1,603.744	1,710.097	1,818.944	6.36%	1.21
-1	1,523.542	1,623.735	1,726.190	6.31%	1.21
0	1,447.832	1,542.252	1,638.721	6.26%	1.21
1	1,376.415	1,465.428	1,556.297	6.20%	1.20
2	1,308.937	1,392.879	1,478.499	6.15%	1.20
3	1,245.161	1,324.345	1,405.042	6.09%	1.20
4	1,184.862	1,259.579	1,335.660	6.04%	1.20
5	1,127.829	1,198.353	1,270.103	5.99%	1.19
6	1,073.773	1,140.350	1,208.028	5.93%	1.19
7	1,022.624	1,085.495	1,149.350	5.88%	1.19
8	974.215	1,033.603	1,093.869	5.83%	1.19
9	928.380	984.494	1,041.390	5.78%	1.18
10	884.970	938.007	991.737	5.73%	1.18
11	843.869	894.013	944.769	5.68%	1.18
12	804.912	852.334	900.294	5.63%	1.18
13	767.973	812.833	858.163	5.58%	1.17
14	732.939	775.387	818.242	5.53%	1.17
15	699.700	739.876	780.403	5.48%	1.17
16	668.143	706.177	744.511	5.43%	1.16

温度 Temp. (°C)	R 最小值 R_Min (Kohm)	R 中心值 R_Cent (Kohm)	R 最大值 R_Max (Kohm)	阻值公差 Res TOL.	温度公差 Temp. TOL.(°C)
17	638.187	674.204	710.473	5.38%	1.16
18	609.742	643.857	678.181	5.33%	1.16
19	582.729	615.051	647.542	5.28%	1.15
20	557.061	587.692	618.457	5.23%	1.15
21	532.668	561.703	590.841	5.19%	1.15
22	509.479	537.009	564.612	5.14%	1.15
23	487.430	513.539	539.694	5.09%	1.14
24	466.455	491.223	516.012	5.05%	1.14
25	446.500	470.000	493.500	5.00%	1.14
26	427.131	449.809	472.507	5.05%	1.15
27	408.711	430.599	452.525	5.09%	1.17
28	391.184	412.312	433.495	5.14%	1.19
29	374.503	394.900	415.368	5.18%	1.21
30	358.623	378.318	398.097	5.23%	1.22
31	343.507	362.526	381.642	5.27%	1.24
32	329.112	347.482	365.959	5.32%	1.26
33	315.398	333.142	351.005	5.36%	1.28
34	302.329	319.472	336.743	5.41%	1.30
35	289.871	306.436	323.137	5.45%	1.32
36	277.995	294.002	310.154	5.49%	1.34
37	266.670	282.141	297.764	5.54%	1.35
38	255.865	270.820	285.933	5.58%	1.37
39	245.556	260.015	274.636	5.62%	1.39
40	235.718	249.698	263.847	5.67%	1.41
41	226.323	239.843	253.535	5.71%	1.43
42	217.356	230.432	243.685	5.75%	1.45
43	208.789	221.438	234.267	5.79%	1.47
44	200.604	212.842	225.261	5.84%	1.49
45	192.784	204.625	216.651	5.88%	1.51
46	185.317	196.776	208.422	5.92%	1.53

温度 Temp. (°C)	R 最小值 R_Min (Kohm)	R 中心值 R_Cent (Kohm)	R 最大值 R_Max (Kohm)	阻值公差 Res TOL.	温度公差 Temp. TOL.(°C)
47	178.180	189.271	200.551	5.96%	1.55
48	171.354	182.091	193.017	6.00%	1.57
49	164.825	175.220	185.806	6.04%	1.59
50	158.579	168.645	178.901	6.08%	1.61
51	152.603	162.351	172.290	6.12%	1.63
52	146.882	156.324	165.957	6.16%	1.65
53	141.405	150.552	159.889	6.20%	1.67
54	136.161	145.023	154.075	6.24%	1.69
55	131.138	139.725	148.501	6.28%	1.71
56	126.327	134.649	143.159	6.32%	1.73
57	121.716	129.782	138.036	6.36%	1.75
58	117.298	125.116	133.122	6.40%	1.77
59	113.062	120.643	128.409	6.44%	1.79
60	109.001	116.351	123.886	6.48%	1.81
61	105.112	112.240	119.552	6.51%	1.84
62	101.383	108.297	115.393	6.55%	1.86
63	97.806	104.513	111.401	6.59%	1.88
64	94.372	100.879	107.566	6.63%	1.90
65	91.076	97.390	103.882	6.67%	1.92
66	87.905	94.032	100.335	6.70%	1.94
67	84.861	90.808	96.929	6.74%	1.96
68	81.936	87.708	93.653	6.78%	1.99
69	79.126	84.730	90.504	6.81%	2.01
70	76.427	81.868	87.476	6.85%	2.03
71	73.847	79.131	84.581	6.89%	2.05
72	71.367	76.499	81.795	6.92%	2.08
73	68.982	73.967	79.115	6.96%	2.10
74	66.688	71.532	76.536	7.00%	2.12
75	64.484	69.190	74.055	7.03%	2.14
76	62.356	66.930	71.660	7.07%	2.17

温度 Temp. (°C)	R 最小值 R_Min (Kohm)	R 中心值 R_Cent (Kohm)	R 最大值 R_Max (Kohm)	阻值公差 Res TOL.	温度公差 Temp. TOL.(°C)
77	60.308	64.753	69.352	7.10%	2.19
78	58.339	62.660	67.132	7.14%	2.21
79	56.443	60.643	64.992	7.17%	2.23
80	54.618	58.701	62.932	7.21%	2.26
81	52.867	56.838	60.954	7.24%	2.28
82	51.180	55.041	59.046	7.28%	2.30
83	49.555	53.311	57.208	7.31%	2.33
84	47.991	51.644	55.438	7.34%	2.35
85	46.481	50.036	53.728	7.38%	2.37
86	45.028	48.487	52.081	7.41%	2.40
87	43.628	46.994	50.493	7.45%	2.42
88	42.276	45.552	48.959	7.48%	2.45
89	40.974	44.163	47.481	7.51%	2.47
90	39.717	42.821	46.053	7.55%	2.49
91	38.507	41.529	44.676	7.58%	2.52
92	37.338	40.281	43.347	7.61%	2.54
93	36.210	39.076	42.063	7.64%	2.57
94	35.121	37.912	40.822	7.68%	2.59
95	34.072	36.790	39.627	7.71%	2.62
96	33.061	35.709	38.474	7.74%	2.64
97	32.086	34.667	37.362	7.77%	2.67
98	31.145	33.661	36.288	7.81%	2.69
99	30.235	32.686	35.248	7.84%	2.72
100	29.357	31.746	34.244	7.87%	2.74
101	28.509	30.838	33.274	7.90%	2.77
102	27.688	29.958	32.334	7.93%	2.79
103	26.896	29.110	31.428	7.96%	2.82
104	26.129	28.288	30.549	7.99%	2.84
105	25.389	27.495	29.701	8.02%	2.87
106	24.672	26.726	28.878	8.05%	2.89

温度 Temp. (°C)	R 最小值 R_Min (Kohm)	R 中心值 R_Cent (Kohm)	R 最大值 R_Max (Kohm)	阻值公差 Res TOL.	温度公差 Temp. TOL.(°C)
107	23.979	25.982	28.083	8.08%	2.92
108	23.310	25.265	27.315	8.11%	2.95
109	22.661	24.568	26.569	8.15%	2.97
110	22.034	23.895	25.849	8.18%	3.00
111	21.425	23.242	25.148	8.21%	3.02
112	20.839	22.611	24.473	8.23%	3.05
113	20.270	22.000	23.818	8.26%	3.08
114	19.719	21.409	23.184	8.29%	3.10
115	19.187	20.836	22.570	8.32%	3.13
116	18.674	20.285	21.979	8.35%	3.16
117	18.176	19.749	21.404	8.38%	3.18
118	17.695	19.232	20.849	8.41%	3.21
119	17.229	18.730	20.310	8.44%	3.24
120	16.776	18.242	19.787	8.47%	3.26
121	16.338	17.770	19.280	8.50%	3.29
122	15.913	17.313	18.789	8.52%	3.32
123	15.501	16.869	18.311	8.55%	3.35
124	15.102	16.439	17.850	8.58%	3.37
125	14.716	16.023	17.402	8.61%	3.40